



SINGLE SHANK RIPPERS



SINGLE SHANK RIPPERS: **100 Series** is ideal for breaking up hard soil or furrowing cultivated soil by adding the optional 12" furrow shovel. Designed for category 1 tractors up to 25 HP. The 1" x 4" shank is adjustable to 19" length for ripping and 15" length for furrowing. The shank is shear-bolt protected and equipped with a 2" wide, hard-faced replaceable point. **200 Series** is recommended for breaking up compacted soil to increase root growth and yield. This rugged built unit is available with a 1" x 6" x 23" shank and designed for category 1 tractors up to 50 HP. The shank is shear-bolt protected and equipped with a high carbon heat-treated replaceable point. **300 Series** is ideally suited to break-up hard and compacted soil for better water penetration and root growth. This unit is constructed of heavy-duty 4" x 8" x 3/8" tubing and is equipped with a 1" x 27" parabolic shank and designed for category 2 tractors up to 75 HP. The shank is shear-bolt protected and equipped with a high carbon heat-treated replaceable point. Models 102L and 300 are Quick Hitch Compatible.

Models	100	200	300
NO. OF SHANKS	1	1	1
FRAME TUBE SIZE	3" X 3"	4" X 4"	4" X 8"
SHANK LENGTH	15" & 19"	23"	27"
HITCH	Cat. 1	Cat. 1	Cat. 2
HP RATING	Up to 25	Up to 50	Up to 75
SHEAR-BOLT PROTECTION	Yes	Yes	Yes
WEIGHT	85	130	240
OPTIONAL 12" FURROWER	Yes	No	No
PARKING STANDS	No	Optional	Optional

Specifications subject to change without notice

Innovative, Rugged & Labor Saving Attachments