



TIRE TRACK RIPPERS



FEATURES:

- Quick hitch compatible
- Two adjustable shanks for ripping soil up to 18" deep
- Adjustable bolt-on shank bracket so they can be set for different tractor tire tread widths

- Shanks are 1" x 6-1/2" wide x 22" long steel
- Main beam 4" x 6" x 1/4" wall tubing
- Parking stand

OPTIONAL EQUIPMENT:

- Hard faced shanks & points

Tractors have to make many passes through vineyards and orchards. This creates hard pan under the tractor tires. From time to time, it is recommended to rip that area to aerate the soil for better water penetration to increase root growth.

The working width of the ripping shanks can be set to the tractor tire centers which shatters the soil over the compacted area up to 18" deep. These rippers have two 4" x 6" beams for added strength. Modes available for all popular vineyard row spacings.

Model	Description	For Row Widths	Beam Width	Adjustable Shank Centers	Hitch	Weight
R2-55	3-Point Ripper	6' (72")	55"	38" to 48"	Cat. 1	320
R2-67	3-Point Ripper	7' (84")	67"	40" to 60"	Cat. 1	350
R2-72	3-Point Ripper	8' (96")	72"	48" to 66"	Cat. 1 & 2	360

Innovative, Rugged & Labor Saving Attachments